

Шаблон style.ini

The `style.ini` is an  [ini file](#) in each [template](#)'s directory¹⁾ configuring the generation of [CSS](#) styles. It has two sections: `[stylesheets]` and `[replacements]` described below.

[stylesheets]

This part defines which CSS files are loaded. Each line is defined as follow:

```
cssfile.css = mode
```

`cssfile.css` is your file name and `mode` is one of the supported output modes as described at [mode](#).

The stylesheet can also be a `.less` file. (See [LESS](#)).

[replacements]

DokuWiki's CSS dispatcher is able to replace placeholders in the loaded stylesheets which are configured through the `[replacements]` section in the templates `style.ini`. This is especially useful for defining a color scheme once and reuse these colors in all files.

These replacements can also be used as [LESS variables](#).

The Styling Plugin let users preview and change the appearance of any template based on the defined replacements. See the [Styling Plugin](#) for details.

Guaranteed color placeholders

The following placeholders are the only ones that are safe to be used by plugins. All templates have to implement these at least, but are free to add more.

placeholder variable	meaning
<code>__background__</code>	main background color
<code>__background_alt__</code>	alternative background color (also used for the theme color in the manifest)
<code>__background_neu__</code>	neutral background color
<code>__border__</code>	border color
<code>__text__</code>	main text color
<code>__text_alt__</code>	alternative text color
<code>__text_neu__</code>	neutral text color
<code>__highlight__</code>	highlighted text color (new since Adora Belle)
<code>__link__</code>	the general link color (new since Greebo)

Template authors should generally try to reuse the placeholder names of the default template.

Example

See for example the [style.ini](#) of the Starter template for an overview of the file. If you are a wiki admin who like to modify the style, please use a [local style.ini](#).

Local style.ini

Local changes can be stored in a local `style.ini` at the location `conf/tpl/<tpl>/style.ini`. (Where `<tpl>` needs to be substituted with the name of the template folder. Just create it if it doesn't exist.)

This prevents losing those changes after an upgrade. The file still needs to include each section (i.e. `[stylesheets]` or `[replacements]`) and paths are relative to the added ini file.

If you use the  [Styling Plugin](#) you can preview and change the replacement values via the admin interface, before it is stored in this file.

Example:

[conf/tpl/dokuwiki/style.ini](#)

```
[stylesheets]
extra.css = all

[replacements]
__text__ = "#000"
__site_width__ = "100%"
```

1)

if the template supports it

From:

<https://wwoss.direct.quickconnect.to/> - **worldwide open-source software**

Permanent link:

<https://wwoss.direct.quickconnect.to/doku.php?id=devel:style.ini&rev=1693220085>

Last update: **2023/08/28 13:54**

